



ENAPART



93 S Railroad Avenue Unit C
Bergenfield NJ 07621 USA
www.enapart.com
sales@enapart.com



Via del Canneto 35,
Borgosatollo, Brescia - Italia
www.enapart.it
vendite@enapart.it



Barbaros Mah. Ihlamur Bul. Aĝaoĝlu
My Newwork No:3/15 Ataşehir / İstanbul
www.enapart.net
satis@enapart.net



PRIVADA 10 B SUR #3908 COL.
ANZUREZ, C.P. 72530, PUEBLA, PUE
www.enapart.com.mx
sales@enapart.com.mx



Friedrich-Ebert-Anlage 36, 60325
Frankfurt am Main, Germany
www.enapart.de
anfrage@enapart.de



4 boulevard Carnot, 95400
villiers-le-bel, Paris, France
www.enapart.fr
sales@enapart.fr



65049, ОДЕСА, ВУЛИЦЯ ІВАНА
ФРАНКА, БУДИНОК 55, ПОВЕРХ 3
www.enapart.com.ua
sales@enapart.com.ua



MUNICIPIUL BUCUREȘTI, SECTOR 3,
B-DUL BASARABIA, NR.250, CORP P+5
www.enapart.ro
sales@enapart.ro



〒584-0023 大阪府富田林市若松町
東2丁目2番16号
www.enapart.co.jp
sales@enapart.co.jp



PLAZA NUESTRA SEÑORA DE LAS
NIEVES 12 ,LOCAL ,50012,ZARAGOZA
www.enapart.es
ventas@enapart.es



Складова база „Онгъл“, Склад А2, п.к.
4006, гр. Пловдив, България
www.enapart.bg
sales@enapart.bg



3 Austin Mews, High Street, Hemel
Hempstead, HP1 3AF , United Kingdom
www.enapart.co.uk
sales@enapart.co.uk

Tridonic

Enapart always strives to provide the competitive prices and timings of supplies for its customers. We sell only original equipment and spare parts, although we are not always the official distributor or manufacturer's dealer. All displayed trademarks and part numbers are the property of their respective owners.

BRAND'S PRODUCTS

| Product | Description |
|---|---|
| P/N: 22185214 Type: PC 1x36 T8 PRO Ip | PC 1x36 T8 PRO sl 220-240V 50/60/0Hz |
| 22185219 | Electronic Ballast |
| 86458601 | |
| ZRM 4.5-ES/C / 12307 | ignitor |
| 87500089 | Igniter |
| P/N: 24138923 Type: DALI USB | PC Interface Module DALI - USB |
| PC 2x14-28 T5 | TOP ip electronic ballast |
| ZRM 20-ES/B | Tridonic Zündgerät für Metaldampflampen |
| 22176712 / RS232 PS/S | |
| 22185109 PCA 2x28/54 T5 EXCEL one4all Ip | Processor-controlled ballast with y II inside |
| (22176495) TE-0060 BASIC 111 | Electronic Transformer |
| P/N: 87500088 Type: ZRM 6-ES/CT | Superimposed ignitor |
| 22185327 Tridonic DALI XC | |
| 22185166 / PC 2x54 T5 TOP Ip | Electronic ballast |
| 22185209 PC 1x80 T5 PRO Ip | Electronic fixed output |
| 9305 SIB 530-250 | Ballast 250W for MH / NAV lamps |
| 22176186 / PC 2/14-35/49/54 T5 PRO-M Ip | Digital Ballast |
| 22176186 | Electronic ballast |
| 89899826 | EM 54/80 - 6 T5 BASIC |
| ZRM 20-ES/B 400 (20826425) | Igniter / Ignitor - Digital Overlay |
| ZRM 20-ES/B 400 ULAG | Zündgerät / Ignitor - Digitales Überlagerungs |
| HSP15223221 | |
| 7714 SI 530-250 TS | |
| 22185105 / PCA 1x35/49/80 T5 EXCEL one4all Ip | Ballast |
| 22185250 PCA | |
| 22154332 Dali-PCDS | |
| P/N: 28000441 Type: DALI PCD 1-300 one4all | Dimmer |
| 22185226 / PC 2x36 T8 TOP sl | |
| P/N: 22185098 Type: PCA 2x80 T5 ECO Ip | |
| 28000093 | |
| 89818655 | |
| 28001253 / LCA 100W 24V one4all SC PRE | LED Driver |
| PC 2x36W T8 PRO | |
| PC 3/4x14 T5 PRO | |
| P/N: 89818662 Type: EM 34B BASIC | Emergency lighting unit |
| OGLS 400W | Vorschaltgerät |

| Product | Description |
|--|--|
| ZRM 6-ES/CT | Overlay igniter with automatic shut-off |
| 28000005 / DALI x/e-touchPANEL 02 | Operating and control unit |
| DLA G1 100mm 1000LM 830 R SNC | |
| DLA G1 100mm 1000LM 840 R SH SNC | |
| 28001092 | |
| DLA G1 150mm 2000LM 840 R SH SNC | |
| 87500446 | LED driver |
| 89818556 / EM 33A BASIC | |
| P/N: 89899951 Type: EM 33A MINI BASIC | |
| 87500259 / PC 2x36 T8 TEC | EVG electronic ballast |
| 89818662 | |
| 22176000 / PC 1x18-24 BASIC sl | |
| P/N: 89899950 Type: EM 34A MINI BASIC | Emergency lighting supply unit |
| P/N: 22176408, Type: PC 1/2x26-42 TC PRO | ballast |
| 86458250 / PCI 1x035 pcb B011 | Digital electronic ballast |
| 89800084 | TBS 3DH4-0T4-SP34 3.6v 4.0Ah Ni-Cd Battery Pack |
| 89800085 / NICD 4A 50 | |
| PC 3/4x18 T8 TOP lp | |
| PC 3/4x14 T5 PRO lp | FL ballasts |
| P/N: 89899886 Type: PC 2X35 - 6 T5 COMBO LP | |
| P/N: 89899698 Type: ACCU - NICD C 6A STICK | |
| P/N: 89899890 Type: PC 2X54 - 6 T5 COMBO LP | |
| 24034323 | |
| 86458342 PCI 0070 FOX B011 | Ballast for metal halide lamps |
| 87500320 | Driver |
| 87500257 | ballast |
| 86457898 | Tridonic Fox Digital Electronic Ballast 70w CDMT |
| 22176002 | Electronic Ballast |
| 28001716 | Control module DALI XC |
| 24138923 | DALI - USB PC interface module |
| P/N: 87500214 Type: PC 4X14 T5 TEC LP | PC TEC series electronic ballast for T5 bulbs |
| 28000211 | |
| 28000661 / LCA 100W 250-700mA one4all lp PRE | Power supply |
| OGLIS 1000W 140 220-240/60 140B194 | |
| P/N: 28001716 Type: DALI XC | |
| P/N: 22176405 Type: PC 1/2x9-13 TC PRO | |
| 86453116 | constant voltage LED operating device |
| 87500463 | LED Driver |
| basicDIM ILD 5DPI 14f | Compact control module with ambient light sensor and motion sensor |
| 86458401 | DALI Repeater |
| PCA 1/36 ECO | |
| PCA 1x36 T8 PRO | |
| P/N: 22185156 Type: PC 2x54 T5 PRO lp | |
| 20560905 | |

| Product | Description |
|---|------------------------------------|
| P/N: 89895960 Type: ACCU - NICD 3A STICK 1X3 | |
| 89800089 / EMAT01226 | cell |
| P/N: 89818655, Type: EM33B BASIC | Emergency lighting module |
| P/N: 87500194 LCI 35W 350/500/1050mA TEC C – 10,15 | Driver |
| 87500570 | Driver |
| P/N: 22185128 Type: PCA 1x26-57 TC EXCEL one4all | |
| LCBI 15W 350mA BASIC PH-CUT SR ADV | |
| P/N: 28000897 Type: DALI MSensor 02 5DPI 41f | |
| P/N: 28000895 Type: DALI MSensor 02 5DPI 41rc | |
| P/N: 28000896 Type: DALI MSensor 02 5DPI 41w | |
| P/N: 28000894 Type: DALI MSensor 02 5DPI 41rs | |
| P/N: 28000647 | remote control |
| PC 3/4x14 T5 PRO lp (22185211) | |
| 22185220 / PC 3/4x14 T5 TOP lp | |
| 28000700 | LED driver |
| 28000701 | |
| 22185228 | ballast |
| 28000310 | ballast |
| 22185164 / PC 2x49 T5 TOP LP | ballast |
| 28000031 | ballast |
| 89800109 | ballast |
| 22185166 | ballast |
| 28000043 | ballast |
| P/N: 87500081 Type: ZRM 2.5-ES/C | Ignitor |
| 22185216 | ballast |
| 22185154 | |
| 87500084 / ZRM 12-ES/C | |
| P/N: 89121840 Type: OGLS 400 C044W 220-240/50 060V150 | |
| 28000041 obsolete | |
| P/N: 89805250 Type: PC 1x36-33 COMBO | Tridonic PC |
| 22185223 | Electronic fixed output |
| 87500605 | |
| 28001663 / LCA 60 W 24 V one4all SC PRE | converters |
| 28001437 / LCA 150W 24V one4all SC PRE | Power supply |
| P/N: 22185218 Type: PC2x58 T8 PRO sl | |
| 28001124 | |
| 28001132 | |
| P/N: 22185120 Type: PCA 1x26-57 TC ECO XitecII | |
| ZRM 4.5-ES/C | Digitales Überlagerungs- Zündgerät |
| 28000655 / LCA 50W 100-400MA ONE4ALL LP PRE | Power supply |
| P/N: 28000039 Type: PCA 2x36 T8 ECO lp xitec II | Electronic Ballast |
| P/N: 87500191 Type: LCI 20W 700mA TEC SR | converter |

| Product | Description |
|--|---|
| P/N: 89800178 Type: EM converterLED BASIC 103 50V | |
| P/N: 22185128 Type: PCA 1x26-57 TC EXCEL one4all xitec II | |
| P/N: 22185221 Type: PC 3/4x24 T5 TOP Ip | |
| P/N: 89899928 Type: PC 2x18-4 TC COMBO | |
| P/N: 89899677 Type: Pack-NiCd 4C 89800334 | |
| P/N: 22185220 Type: PC 3/4x14 T5 TOP Ip | |
| P/N: 22185166 Type: PC 2x54 T5 TOP Ip 89800206 | |
| P/N: 28001071 Type: LCA 60W 350-1050mA one4all C PRE OTD 28001074 | |
| 22176407 / PC 1/2x18 TC PRO | |
| P/N: 89899928 Type: PC 2x18-4 TC COMBO 220-240V | |
| P/N: 24166311 Type: LCI 005/0350 E020 | |
| P/N: 87500192 Type: LCI 35W 350mA TEC C PC258 T8 Pro Art.Nr.: 87500573 | |
| 28001662 / LCA 35W 24V one4all SC PRE 28001663 | Driver |
| 28001437 | Driver |
| 28000045 | Electronic ballast |
| 89800453 | PC 2/36 T8 Industry |
| 28000876 (alt: 86458559) | Power supply |
| P/N: 28000413 Type: LCU 96W 24V SR TOP 89899890 | DRIVER |
| PC 3/4x18 T8 TOP Ip (22185228) 22176077 | High-Frequency Electronic Ballast |
| 22176078 | PC 1/30 T8 PRO |
| P/N: 22185210 Type: PC 2x80 T5 PRO Ip 28000412 | PC 2/30 T8 PRO |
| P/N: 22185227 Type: PC 2x58 T8 TOP sl 28000047 | Constant voltage LED control gear |
| 89818556 | Module |
| 20820138 | |
| 28002773 | Accu-NiCd 3A 55 |
| LC 15/350/43 fixC SC SNC2 (87500729) | DRIVER |
| P/N: 22185108 Type: PCA 1x28/54 T5 EXCEL one4all Ip Xitec II 28000713 | constant current led driver |
| 28000690 LC | |
| P/N: 89899611, Type: EM14BBASIC-TR 28002470 | Emergency unit for luminaire Constant current LED driver |

| Product | Description |
|---|---|
| 87500336 | LED driver |
| 22185157 / PC 1x14-35W T5 TOP Ip | electronic ballast |
| 87500386 | Driver |
| P/N: 22185209 , Type: PC 1x80 T5 PRO Ip | Ballast |
| 28002302 | |
| 28001073 | |
| 28000690 / LC 100W 250-700mA flexC Ip EXC | constant current led driver |
| 22185217 / PC 2x36 T8 PRO sl | Electronic Ballast |
| PCA 1x18/24 TCL EXCEL one4all c ,(Art.Nr. 22185251) | ELCTRONIC BALLAST |
| 28001108 | RESISTANCE I-SELECT 2 PLUG |
| 28001036 | |
| 28000657 | Ballast |
| 87500621 | Current Led Driver |
| 87500733 | LED DRIVER LC 25/500/43 |
| 87500735 | LED DRIVER LC 25/700/36 |
| 87500737 | LED DRIVER LC 30/500/54 |
| 28002417 | DRIVER LC 100W/24V BDW SC PRE |
| 87500734 | DRIVER LC 25/600/42 FIXC SC SNC2 |
| 28000672 | DRIVER |
| 28001571 | DRIVER |
| 28000674 | Driver |
| 28001253 | Driver |
| 28001570 | driver |
| 28000676 / LCA 45W 500-1400MA ONE4ALL SC PRE | Power supply |
| 28000675 | Driver |
| 28000667 / LCA 60W 900-1750mA one4all C PRE | Driver |
| 28000665 | DRIVER LCA 25W 350-1050MA ONE4ALL C PRE |
| 22185209 | Electronic ballast |
| 87500774 | |
| 87500629 | Driver |
| 87500559 | Driver |
| 87500566 | power supply |
| 87500838 | Driver |
| 87500835 | Driver |
| 89800206 / EM 06 PRO G2 | emergency conversion kit |
| 22185226 | Electronic Ballast |
| 22185096 | BALLAST |
| 89800108 | Basic kit unit |
| 22185225 | |
| 28002746 / SLE G7 17mm 5000lm FASHION H EXC | LED Modules |
| 22185121 | |
| 87500256 / PC 2x18 T8 TEC | |
| 22185102 | |
| 22185237 / DALI-RM/S 4x10A | |

| Product | Description |
|---|--|
| 89800308 | |
| 89800459 | Fluorescent tube |
| 22185107 / PCA 2x80 T5 EXCEL one4all Ip xitec II | |
| 22185099 | |
| 22185100 | |
| 22185097 | ballast |
| 28000037 | |
| 28000035 | |
| 22185095 / PCA 2x14/24 T5 ECO Ip | |
| 89818236 | EMERGENCY MODULE & BALLAST |
| Art.Nr.28000706 (LC 25W 350-1050mA flexC SC EXC) | LED Driver |
| 28000694 (LC 25W 350-1050mA flexC C EXC) | |
| 28000695 (LC 45W 500-1400mA flexC C EXC) | |
| 28000707(LC 45W 500-1400mA flexC SC EXC) | |
| 22185214 | |
| 28002469 | |
| 28002494 | |
| 22 176 107 | Compact electronic starter for fluorescent lamps with fixed output Tridonic PC TC PRO |
| p/n: 28000538; Type: LCI 100W 350mA-900mA | |
| P/N: 87500921, Type: LC 20W 100-1050mA 44V o4a NF SR EXC3 | LED driver |
| PCA 2x80 T5 ECO Ip | |
| PCA 2x21/39 T5 ECO Ip | |
| PC 2x36 T8 TOP sl 22185226 | ballasts |
| 28002091 / ACCU-NiMH 2.2Ah 6A | |
| 28002383 / SPD 10kV CE SNC | Surge protection |
| 89800687 | emergency lighting driver/inverter |
| 28000666 | Driver |
| PC 4/14 T5 Ar.N:22 068 976 | |
| Type LC 40W 900mA fixC C SNC / 87500560 | Driver |
| 20296024 / OGL 250 W 30 220-240/50 030A084 | |
| OGLIS 250W 40 230-250/50 040A094 TP | |
| 20820138 / OGLS 400W 60 220-240/50 060A114TP | |
| 20296030 / OGL 400 W 40 220240/50 040A094 | |
| 28003210 / LC 14W 250-350MA FLEXC R ADV2 | Power supply |
| PC 1/58 T8 TOP SL | |
| p/n: 28000936; Type: 5DPI 14rc | M Sensor |
| 24138830 / PC 1x5-16 W BASIC | electronic ballast |
| LC 10/250/40 fixC SC SNC2 (87500795) | Tridonic LED-Driver |
| LC 35/200-350/121 flexCC Ip SNC3 (28003376) | Power Supply |
| P/N: 28003377, Type: LC 50/200-350/170 flexCC Ip SNC3 | LED driver |
| 22176000 / PC 1x18-24W BASIC sl | |
| 28001807 | Power Supply |

| Product | Description |
|--|---|
| OGL 1000W 120 | |
| 28002238 | |
| 20880891 | ballast |
| Art.N: 24138831 | PC4-13 electronic ballast |
| 87500507 / PC 1/36 TCL PRO | Electronic Ballast |
| 28002300 | constant current converter |
| 22185148 / PC 2x14-35 T5 PRO Ip | High Frequency Ballast |
| 28001911 / LCA 100W 350-1050mA 2xDT8 Ip PRE | PRE LED DRIVER |
| 28000673 / LCA 10W 150-400mA one4all SC PRE | LED-driver |
| 87500225 / LCI 35W 700mA | LED converter |
| 28001953 | |
| 87500747 | |
| 28000672 / LCA 45W 500-1400mA one4all SR PRE | |
| 87500781 LC 38/700/54 fixC Ip SNC2 | |
| 87500089 / ZRM 12-ES/CT | igniter |
| 28001847 / DALI Interface RS232 PS/S | |
| PCA 2/26 TCD ECO/22084752 | |
| LC 25W 350-600mA | Netzteil: Impuls; LED; 25W; 27÷44VDC; 350÷600mA; 198÷264VAC; IP20 |
| 28001920 | 35W 24V Constant Voltage LED Driver |
| 89603341 | |
| 87500717 / LCO 90/200-1050/165 o4a NF C EXC3 | led driver |
| 28000876 / DALI PS2 | power supply |
| 87500744 / LC 40/900/45 FIXC SC SNC2 | LED driver |
| 28000882 / DSI-V/T | LUX CONTROL |
| 22185100 / PCA 2x28/54 T5 ECO Ip Y II | |
| 28002103 / LLE FLEX G1 | LED module |
| 28000022 / DALI Touchpanel 02 | |
| 24166012 | mains adapter x-touchPANEL |
| P/N: 28002774, Type: Accu-NiCd 5A 55 | cell |
| 89800564/21346035 | EM converter |
| PN: 22185217 / Type: PC 2x36 T8 PRO sl | high frequency ballast |
| 87500716 | LED Driver |
| 87500274 | LED-Treiber |
| 87500283 | |
| 87500578 / LC 10W 500mA fixC C SNC | constant current driver for luminaire installation |
| 87500509 / PC 1/55 TCL PRO | |
| 87500447 / LC50W 700mA fixC Ip SNC | |
| P/N: 28001250, Type: LCA 75W 250-550mA | LED driver |
| 89800563 | emergency light LED-Driver EM converterLED BASIC 204 NiCd/NiMH 250V |
| P/N: 87500083, Type: ZRM 6-ES/C | |
| 89800649 | converterLED |
| 87500995 | LED drivers |
| 89800650 | EM converter |

| Product | Description |
|---|--|
| 87500921 / LC 20W 100-1050mA 44V o4a NF SR EXC3 | LED-Driver |
| PC 124T5PRO LP (22 087 891) | |
| PC154T5PRO LP (22 176 140) | |
| 28000683 / LC 75W 350-1050mA flexC lp EXC | led driver |
| 28002487 / LC 40W 900mA fixC SC ADV | |
| PCA236T8ECO-TR | digital dimmable ballast |
| 87500797 | Driver |
| 87500728 | |
| 89800574 | |
| 28003431 SLE G7 | |
| 28002087 | |
| 28000657 / LCA 75W 100-400mA one4all lp PRE | Power supply |
| 28002306 | Power supply |
| 87500726 / LC 50/250-400/140 o4a lp ADV | |
| 20569782 / OMBIS 35 B103W 230-250/50 035A097T | ballast |
| PC 1x18W T8 TEC / 87500255 | |
| 28000674 / LCA 17W 250-700mA one4all SC PRE | Driver |
| 87500994 | Linear drivers |
| 87500994 LC 50/200-350/170 flexC lp SNC4 | |
| P/N:87500766 , Type: LC 50/1200/42 fixC SC SNC2 | driver |
| 28002465 / LC 38W 250-350mA flexC lp ADV | Power supply |
| 28002269 / DALI-PCD 1-300 one4all G2 | Phase and section dimmers |
| HF118-24L TRI | |
| 28002214 | lighting management |
| 28002496 / LC 20W 350/500/700mA flexC SR ADV | driver |
| P/N: 20821676, Type: EC 13 A27 230V 10/13W | lamp |
| 89800645 / EM converterLED PRO 305 MH/LiFePO4 250V | Self-contained emergency |
| 89800574 / EM converterLED BASIC 203 NiCd/NiMH 250V | Emergency lighting LED driver for manual testing |
| 87500782 / LC 57/1050/54 FIXC LP SNC2 | LED switching power supply |
| 87500095 / ZRM 12-ES/C 400 | Standard ignitor |
| 28000510 | LED Driver |
| 28000508 | Led driver |
| 87500467 / LC 65W 700mA fixC lp SNC | Led luminaire ballast |
| 28002053 / LCI 150W 325-1050mA 300V o4a sl PRE | Driver |
| 28002467 / LC 71W 250-350mA flexC lp ADV | Driver |
| 22176182 | |
| 22088937 PC 2/18 TCD PRO | |
| 87500258 PC 1x36 T8 TEC | |
| 4014001 | ballast |
| 87500757 | power supply |
| 87500087 / ZRM 4.5-ES/CT | Digital superimposed ignitor with timer |
| 89800558 | EM convert emergency lighting control unit |

| Product | Description |
|--|--|
| LC50W100 | LED Driver |
| P/N: 28004411, Type: LC 55/350-1050/54 flexC NF h16 EXC4 | Driver |
| P/N: 87500607, Type: LC 75W 350MA FIXC LP SNC | power supply |
| DFX 530-18 (7727) | Power Supply eletr. |
| 24166332 / LCU 150/12 E020 120-240V | LED Driver |
| LC 25/350/71 fixC SC SNC2 (87500732) | |
| LC 57W 800-1050mA flexC Ip ADV | LED Constant current LED driver for luminaire installation |
| 28000681 | power supply |
| 87500292 | Top Low Profile |
| TBS 4SCH1-5T4-SP34 / 89899692 | Battery Pack |
| OGLI 2000W 160 | |
| 28002475 | |
| 87500665 | |
| 87500666 | |
| 137946HTC | |
| 89805272 | |
| 913713028366 | |
| 1x21/39 T5 ECO IP 22185101 | |
| P/N: 87500851, Type: LC 85/1200 | LED-Treiber |
| 89800385 | Emergency lighting battery |
| LC 60W 24V SC SNC | |
| 28000201 / LCI 65w 150mA-400mA TOP Ip | |
| 28003375 / LC 25/200-350/70 flexCC Ip SNC3 | Power supply |
| 28000660 / LCA 75W 900-1800mA one4all Ip PRE | LED driver |
| P/N: 22176211, Type: PCA 3X14/24 T5 Eco Ip | electronic ballast |
| 87500668 | |
| BCS49.1FX-11/220-240 | |
| Accu NiCd 4A 50 | |
| 28001808 | |
| 89603037 | |
| 87501098 | |
| 28002924 | |
| 22185216 / PC 2x18 T8 PRO Ip | |
| 87500831 | |
| 89800092 | |
| 28002416 | LED driver |
| 87500752 | Power supply |
| 28001983 | |
| 87500783, Type: LC 75/1400/54 fixC Ip SNC2 | LED switching power supply |
| 28004038 / LCI 150W 250-1050mA pD NF h28 PRE4 | Industry linear dimming |
| 28003557 | LED driver |
| LC 35W 24V SC SNC2 | |
| 28000039 / PCA 2X36W T8 ECO IP | Ballast |
| HF-P 249 TL5 HO III 220-240V 50/60Hz IDC | |

| Product | Description |
|--|--|
| 913713034166 | |
| 89800432 / EM powerLED ST FX 103 SR NiCd 45W 50V | emergency light LED-Driver |
| PACK-NiCd 4D | Battery pack |
| 4350000 | |
| 4345000 | |
| 87500726 / LC 50W 250-400mA 140V o4a Ip ADV | power supply |
| AD148 28003377 LC 50/200-350/170 flexCC Ip SNC3 | |
| 28004618/ LED-Driver LC 40W 75-400mA 230V bDW NFC h16 PRE4 | LED driver |
| DALI XC G3 CWM 30 DA2 | Control module |
| AB516 28005113 LC 75/350-550/216 flexCC Ip SNC4e | LED driver |
| PC 1x38 - 34 HO DD COMBO / 89899933 | |
| 28000705 | LED ballast |
| LC 25/500/43 fixC SR SNC2 / 87500751 | |
| LLE G2 (28002916) | |
| LLE G2 (28002913) | |
| 28004119 / LC 10/200-350/29 flexC Ip SNC4 | Linear driver |
| 89805277 | Test switch |
| 87500832 / LCO 90/200-1050/165 pD+ NF C PRE3 | LED-Driver |
| AD820 28003555 LCO 75W 200-1400mA flexC 0-10V NF L SNC3 | |
| ELTR04625 | |
| 28002472 | LED-Driver LC 19W 250-350mA flexC Ip ADV |
| 22 176 169 | Ballast |
| 23568729/Elpro ELB DALI T8 2X36W (QTIDAL - 20009012 | |
| 87500826 | LED driver |
| 28005037 / LC 90W 200-800mA flexC NF h16 EXC4 | LED driver |
| 89899605 | LED EM green |
| LCO 90/200-1050/165 NF C ADV3 | |
| 87501100 | LC 60/200-350/200 flexCC Ip SNC4 |
| 87501101 / LC 75/350-500/216 flexCC Ip SNC4 | Power supply |
| 89800559 | emergency light LED driver EM converterLED BASIC 203 NiCd/NiMH 50V |
| PCA 2/36 TCL EXCEL one4all | Ballast |
| 87501147 / LC 30W 350-700MA DA SC SNC4 | |
| 87501146 / LC 15W 100-400MA DA SC SNC4 | |
| 89800560 / EMTR00560 | EMconverterLED |
| 28004142 | LC 38W 400-700mA flexC Ip SNC4 |
| 89800559 / BASIC 203 NiCd/NiMH 50V | Emergency lighting LED Driver for manual testing |
| TE-0105 | Transformer |
| 37968/155 MBQ 155/2 TCI SRL | |
| LCA 85W 600-1800mA DT8 Ip PRE | |
| 28004120 | |
| LC 25W 100-500MA FLEXC LP EXC | driver |

| Product | Description |
|---|-------------------------------|
| LLE 16X560MM 2400LM 830 HV ADV5 | led strip |
| 87500344 LC 40W 900mA fixc SC ADV | |
| 87501085 / LC 42/900-1050/42 FLEXC SC SNC4 | Power supply: switching |
| 89603425 | |
| 87501119 | |
| 28000680 | |
| 28000679 | |
| 28001035 | |
| 28001105 | |
| 28005015 | |
| 28001101 | |
| LC 100W 24V 0-10V Ip SNC UNV - 28002852 | LED-Driver |
| 28004144 | |
| 28004412 | |
| 28003163 / LCO 135/200-1050/22 | |
| LC 50/350/143 FIXC LP SNC2 | power supply |
| 87501146 / LC 15/100-400/42 DA SR SNC4 | LED driver |
| LC 10/350/29 fixC SR SNC2 | |
| 28004433 | |
| 87500921 | |
| Ombis 35 a604w 220-240//50 030a098t 1x35w x lamp hs//hi | |
| 137945HTC | |
| 87500850 | LED-Driver |
| 28005013 | LED STRIP |
| EC 22/30 A50 | wire wound switch start choke |
| ELTR00018 | |
| 380MZN2000S-BG | |
| basicDIM ILD 16DPI 69f | |
| 28004037/ LCI 150/250-1050/300 o4a NF h28 EXC4 | |
| EL1/18NGN | |
| LC 50/200-350/170 | |
| LC 10W 350MA FIXC C SNC/ 87500577 | Compact drivers |
| AD010 87500796 LC 10/350/29 fixC SC SNC2 | |
| LC 75/1100-1400/54 FLEXC LP SNC4 | Power supply: switching |
| EL2X14-35iDim 220-240V 50-60Hz 840 Helvar GmbH | |
| 28003389 / basicDIM ILD G2 SFI 20 5DPI WH | Sensor |
| 28004235 | |
| 28003602 | |
| LC 45/450-1050/54 o4a NF SR EXC3 | LED driver |
| P/N: 22176409, Type: PC 1x57/70 TC PRO | HF ballast |
| 28005039 (LC 120/350-1050/240 flexC NF h16 EXC4) | |
| AD177 28003297 LC 100W 24V IP67 L EXC UNV | |
| 89899878 | ballast |
| PCA 2/36 | ballast |

