



ENAPART



93 S Railroad Avenue Unit C
Bergenfield NJ 07621 USA
www.enapart.com
sales@enapart.com



Via del Canneto 35,
Borgosatollo, Brescia - Italia
www.enapart.it
vendite@enapart.it



Barbaros Mah. Ihlamur Bul. Aĝaoĝlu
My Newwork No:3/15 Ataşehir / İstanbul
www.enapart.net
satis@enapart.net



PRIVADA 10 B SUR #3908 COL.
ANZUREZ, C.P. 72530, PUEBLA, PUE
www.enapart.com.mx
sales@enapart.com.mx



Friedrich-Ebert-Anlage 36, 60325
Frankfurt am Main, Germany
www.enapart.de
anfrage@enapart.de



4 boulevard Carnot, 95400
villiers-le-bel, Paris, France
www.enapart.fr
sales@enapart.fr



65049, ОДЕСА, ВУЛИЦЯ ІВАНА
ФРАНКА, БУДИНОК 55, ПОВЕРХ 3
www.enapart.com.ua
sales@enapart.com.ua



MUNICIPIUL BUCUREȘTI, SECTOR 3,
B-DUL BASARABIA, NR.250, CORP P+5
www.enapart.ro
sales@enapart.ro



〒584-0023 大阪府富田林市若松町
東2丁目2番16号
www.enapart.co.jp
sales@enapart.co.jp



PLAZA NUESTRA SEÑORA DE LAS
NIEVES 12 ,LOCAL ,50012,ZARAGOZA
www.enapart.es
ventas@enapart.es



Складова база „Онгъл“, Склад А2, п.к.
4006, гр. Пловдив, България
www.enapart.bg
sales@enapart.bg



3 Austin Mews, High Street, Hemel
Hempstead, HP1 3AF , United Kingdom
www.enapart.co.uk
sales@enapart.co.uk



Weigel

Enapart always strives to provide the competitive prices and timings of supplies for its customers. We sell only original equipment and spare parts, although we are not always the official distributor or manufacturer's dealer. All displayed trademarks and part numbers are the property of their respective owners.

BRAND'S PRODUCTS

Product	Description
023.130.0609	WQ96/2S Dual Voltage Meter AC
UMU05-3261110	Transmitter for current, voltage and auxiliary energy.
652.10.121600 / SUS-95-Q R/G 220VDC	LED switching position indicator
685.130.9291 (Skala: 0-150 Grad C)	moving coil
684.130.1000 (EQ96K, Wandler 1200/1 A)	Moving iron instrument
A1U2.2 / IMU02-6261120	Measuring transmitter for current, voltage with auxiliary energy
PI 24-1	Switch Position Indicators
644.0251	Mechanical Control Indicator
MaxX 125 Lasthebemagnet Flachmaterial: 125 kg Rundmaterial: 50 kg	Lasthebemagnet
MaxX 250 Lasthebemagnet Flachmaterial: 250 kg Rundmaterial: 100 kg	Lasthebemagnet
DPA10-30/E10R-7	Digital built-in meter
DSA13-NA30/A10R-08 (645.1312.02)	DSA13-NA30/A10R-08
DPA10-31/E10R-7 (645.1213.1007)	Digitales Einbaumessgerät
645.1214.1007 DPA10-40E10R-7	Digitales Einbaumessgerät
DPA14-40/A10R (200.1314.1008)	Digitales Einbaumessgerät
PQ72K (685.120.0632)	Drehspulinstrument DC
685.130.9291 (Skala: 0-10 bar)	moving coil
DSA13-NA30/A10R-08	
V1U2.2 (DC 24V(20...72V)	
PMU12-15B12150W0001	
194.933.0700	three-wire mains of any load
652.01.121600	LED Schaltstellungsanzeiger
652.02.121600	LED Schaltstellungsanzeiger
WQ144/2S	Double voltage gauge
SUS-01-Q R/G 220V DC	
SUS-01 R/G 220V DC	
UMU05-9221110-0002	AC current transducer
416.134.10	
416.134.1000	
416.134.3629	
644 0291 PI29-1	Switch position indicator mechanical
644.0361	Switch position indicator mechanical DC
PI 29-1 / 644.0291	Switch position indicator
PI 36-1 (644.0361)	Position Gauge



Product	Description
674.134.2000	Panel ammeter
474.130.10	Panel WATTMETER
432.130.35	Analog Pointer-Type Frequency Meters 90 or 240 Dial
PQ72K Drehspulinstrument DC	
PIR 25-1 (644.1251)	Switch Position Indicator
81BA14060406	Drehspulinstrument DC
PQ96K (MB: 0...30V)	rotary coil instrument
PQ96K (MB: 0...60mV an NW)	rotary coil instrument
800.7327	
EQ96K	Double tongue frequency meter
BIEQ72K Bimetall-Dreheiseninstrument AC (674.124.1000)	Amperemeter
675.130.0624	
801.7327	
E-1005-0018-00	
SUS-02-Q R/G 220VDC	
SUS-02 R/G 220VDC	
VSA 03 VRT-6	Full wave soft starter
SUS-01-T R/G/Y 125VDC	LED switch position indicator with LED test
Type PQ96K	
620.0071 Type Typ S= NiCriNi	
023.130.4687	Double voltmeter
FQ96/2 031.130.0161.00	
FQ96/2 031.130.0163.00	
415.140.35 , type VQ144K	Drehspulinstrument mit Gleichrichter AC
031.130.0164.00	Frequency meter
194.934.0220	Four-wire three-phase system
685.130.9291/Skala: 0-25 MW	Control panel instruments
685.130.9200 PQ96K	
685.130.9291 (Skala: 0-100 %)	
685.130.9291 (Skala: 0-200 %)	
685.130.9291 (Skala: 0-60 MW)	
Sy144S	Synchronoskop
685.130.9291/ Skala: -15....0....15 MVar	moving coil
685.130.9291/ Skala: -7...0...7 MVar	moving coil
432.130.10	moving coil
685.130.9291/ Skala: cap. 0,5-1-0,5 ind	moving coil
040.110.10	Hour meter
031.130.0163.00	frequency meter
LSP96 Skala: 0...1800rpm	
LSP96 Skala: 0...650 ohne Messgröße	
LSP96 Skala: 0...70 Grad C°	
SUS-01-Q G/R 24V DC/652.02.211200	
PI 24-2	Switch Position Indicators
BiEQ 96K	Amperemeter



Product	Description
03CA50590716	
644.0241	
644.0242	
SUS-01-T-R/G-110VDC	Switch Position Indicators
SUS-01-T-Q-R/G-110VDC	Switch Position Indicators
VQ72K (415.120.20)	moving coil
PQ48K / 01AA10130013	moving coil
SUS-01-Q	LED switch position indicator
SUS-01	LED switch position indicator
PQ96K / 81CA14061366-00840	.
VSA 05-6 VR	
684.130.0635	Moving iron instrument
81CA13020709	AMPERMETER ANALOG
685.130.0632	VOLTMETER / ANALOG
800.7321	
800.7328.1	
SUS-01-T-Q-R/G/Y-220DC (652.04.121650)	Switch Position Indicators
SUS-01-T-R/G/Y-110V (652.03.120450)	Switch Position Indicators
DUW2.2	Three-wire three-phase network of any load
Artikel 644.0255 Typ PI 25-5 p/n 181.975.9202.5 Type V1U2.2	Switch position indicator mechanical DC
EQ72K (674.120.0622)	ANALOG VOLTMETER
DPA20-40/A20R-4	digital indicator
652.02.211200 (SUS-01-Q G/R 24VDC)	LED switch position indicator
684.130.1000 (EQ96K, Wandler 1500/1 A)	Moving iron instrument
DPA20-50/A20R-4	Digital mounting gauge
684.130.1000, Type: EQ96K	Rotary iron instrument
684.130.3629, Type: EQ96K	Rotary iron instrument
652.01.211200, Type: SUS-01-G/R-24VDC	LED Switch Position indicator
652.02.211200, Type: SUS-01-Q-G/R-24VDC	LED Switch Position indicator
020.130.3629, Type: WQ96RS	Rotary iron instrument
031.130.0163.00, Type: FQ96/2	Dual Tongue Frequency Meter
P/N:194.934.0240-0001 Type:VUW2.2	Four-wire three-phase network of any load
VUW2.2 (500/5 A)	Four-wire three-phase network of any load
EQ72K (684.120.2000)	Ampermeter
EQ72K (684.120.0635)	Ampermeter
010.230.9291, Type: P96PRS old code new code 55IA10591709-00151	profile - moving coil instrument DC
674.130.1000	Moving iron instrument AC
E-1005-9021-00	
685.130.9291	
E-2008-0010-01	
644.0291	switch position indicator
Nr. 644.0361 / Type PI 36-1	Switch position indicator
VSA 05 VRT	Full-wave soft starter



Product	Description
PIR 36-1 (644.1361)	Switch Generation Indicators Mechanical AC
644.1291 / PIR 29-1	Mechanical switch indicator AC
080.130.0609	synchronoscope
652.01.211200/SUS-01 G/R 24VDC	.
DMA 14-31-D 20 R-S1	digital display
675.130.9291	
PQ72K (MB: 0-20mA)	Analog Meters with Moving-Coil Movement 90° Dial
SUS-99-GS-02 24VDC	led indicator
SUS-99-GS-01 24VDC	LED indicator
PI 25-1 / 644.0251	Switch position indicator
PI 29-1	
PI 39-1	
Pw-MU	CONVERTER
PQK48 / 25A	
PQK48 / 40V	
644.0362	Switch position indicator
35CA14200420-00642	
V1U 2.2	
IMU02-422113	
VQ96K 0-500VAC DIRECT	
Q96/Q144-K (MA96A008)	
WQ96RS 0-10AAC DIRECT	
VSA 03 VRT-7	
SUS-95-Q-R/GS 230V	SYGNALIZATOR
SUS-95-R/GS 230V	SYGNALIZATOR
BIEQ 72 K / 10BZ11510171	
PQ72K 4-20MA	Analog percentage load indicator / motor percentage indicator
P/N:194.934.0700-0002 Type:VUW2.2	
SUS-01-Q-T-R/G-12	POS. INDICATOR LED
SUS-95-Q-L R/G 230VAC P30	
SUS-95-Q-L R/G 230VAC P30 (1 pc)	
SUS-95-Q-L R/G 230VAC P30 (50 pcs)	
SUS-95-Q-L R/G 230VAC P30 (100 pcs)	
100.140.00.02 / WA 144-B	
UMU05-9221130-0004	
56GA10620062-00151	
56GA14060630-00151	
800.7417	Shunt
800.7416	Shunt
800.7339	Shunt
56GA10620062-01211	
56GA14060630-01211	
56GA10620062-00305	
56GA14060630-00305	
EQ96KL	PANEL MOUNTED INSTRUMENT



Product	Description
FQ96/2	Double frequency meter 2x45-55Hz, 120V
SY96S	Synchroscope 2x120V, 50Hz
WQ96/2S	Double voltmeter 2x120V
SY 144 S (50 Hz)	synchroscope
SUS-99-Q-L G/R 220DC	
EQ72K	
80CA11560182	Analog measuring devices with rotary iron meter
80BA11610161	Analog measuring devices with rotary iron meter
80BA11590159	Analog measuring devices with rotary iron meter
55IA10591709-00151	
EQ96K (0V TO 300V)	VOLT METER
EQ96K (0V TO 900V)	voltmeter
Type: AUE 2.2	
VUD 2.2 / 27050459	Transducers for Current, Voltage requiring Auxiliary Supply
Front glass for BIEQ96	BIEQ96 front glass assembled
A1U2.2/ IMU02-6261110	
SUS-01-T G/R 125VDC	LED switch position indicator
SUS-01-T-Q-R/G 125VDC	LED switch position indicator
10BZ11510171	Analog meters
10CZ11510171	Analog meters
EQ 48 K 0...250V	ammeter
EQ 48 K 0...500V	ammeter
EQ 48 K 0...50/5A	ammeter
BIEQ96K (10CZ11560169)	Analog measuring devices with bimetallic and bimetal rotary iron measuring device
EL19-00313 / 81CA14180418	ANALOG VOLTMETER
RP96MIN/MAX	a display with 2 thresholds
652.02.121400/SUS-01-Q R/G 110VDC	
652.01.121400/SUS-01 R/G 110V DC	LIGHT INDICATOR FOR 2 POSITIONS
YDEVANA	TRANSDUCER
TD497193 / BIEQ96K	Analog measuring devices with bimetallic and bimetal rotary iron measuring device
TD497194 / EQ96K	Analog measuring devices with rotary iron meter
IMU02-6261150	transducer
SUS-01-Q- T-R/G-125VDC	LED switch position indicators and LED lights
35CA30581061-01317	Analog instrument
81BA10591000	
PQ96K MB:0-10A SK:0-10A	
EQ72K 150/5A	Analog Meters with Moving-Iron Movement 90° Dial
IMU02-1110	Transmitter for AC or AC voltage without auxiliary energy
IMU02-4261110	transducer
UMU30-3062130	
81BA14061000	Rotary coil measuring system 90° scale
PMU14-15511110-0004	transducer
644.0291.FZ	Switch position indicator



Product	Description
652.12.121	
DPA14-30A10R-4	Watch
652.18.201400	position indicator/switch
611A14370437	
611A17070707	
PIR24-5	Mechanical position indicator, light background separation symbol, 24-230V AC
PIR24-1	Mechanical position indicator bar symbol, 230VAC
81CA10590158	
34CA10590413-01719	
652.03.211500	
UMU05-9261110-0002	
SF6.0413	
652.04.121500	LED INDICATOR LIGHT
34CA10590708-01719	
81CA14060406	
56FA10591000-00305	Analogic Indicator
PI 24-5	Switch position indicator
80BA15510555	Weigel; back wall cover
F-1004-0080-00	
old code 181.975.9202.5 Type V1U2.2/new code UMU05-92F1150-0008	
DPA14-40F10R-4	
PQ96K / 81CA14200420	Rotary coil instrument DC
80CA14200420	Voltmeter
80CA14151864	
80CA11510168	
80CA11510182	
80CA11511977	
SUS-99-Q-R/G	
80CA11560171	Ampmeter
80CA14141805	voltmeter
652.04.211500	
45CA14130413	
46CG16020602	
IMU02-42F1150	
UMU05-72F1150	
56GA14301751	Panel indicator
81CA10591223-01941	TRANSFORMER STEP INDICATOR
SUS-01-T-R/G-125V DC	
PIR 25-5	Switch position indicator
PMU11-15B12450W0002	
PQ72K 0-50mA	analog meter
81AA14062174	Analog potentiometer
81BA14062752	Analog ammeter



Product	Description
80BA11560172	
81BA10580058-00624	Analog measuring devices with 90-scale rotary coil meter
81BA30591002-01007	ANALOG METER
80CA17010719	
81BA14061267/PQ72K	
81BA14060784-02056	
EQ96K - MB: N/100V, SK:0..20/24kV	
DMA14-31E20R-S1/645N0104.1044R-001	digital display
PQ48K	Ammeter
PMU11 (MWg-3.1) [DGW 4.0]	
SUS-01-Q G/R 110VDC P30	.
SUS-01 G/R 110VDC P30	.
46CJ16020602 / Type: FQ96	terminal cover
SQ 0204 / 643.130.0204.110	Synchroscope
01AA10130013	
80CA14170417	
42LA01560171	
EQ48K-200/5A	.
EQ48K-25/50A	.
EQ48K-50/5A	.
FMU08-14440	
81BA50592992-00148	
PMU16-11412440W0001	
38CA51580158-02419	
38CA51560174-02420	
53CJ16000901	
45CA14153202	
45CA14153203	
PQ96K / 81CA10591223-01941	
03CA10590716 / LSP96K MB	transducer
667.38175-HG210/ AR 96 Size 96x96m	GLASS COVER FOR 96X96MM PANEL METER
01AA10130013/PQ48K, MB+SK: 0-40µA	
80BA14190419/EQ72K, MB: 0..500V, Sk: 0..500V	
EQ96K 0-2000/2400A	
WQ 96RS 0-10/12kV	
UMU05-42F1150	transducer
35CA50600650-01853	
643.130.0204.100	Synchroscope with LED display
DPA10-30E 10R	
80CA51560190	
SUS-01-Q R/G 110VAC	
200.1314.1004	Digital built-in meter
801.7324	
34DA10601000-00901	
PI 25-2	Mechanical semaphore indicator



Product	Description
PQ72K, MB:0-10V, SK:0-45t (81BA54061366-00840)	
LSP 96 K	
SUS-99-L-R/G-110DC	
80CA11510180	
80CA14260426	
80CA11510169	
80CA11510001	
06BA54190419	Switched 400V Voltmeter
80BA51960188 - 0..1/1,2A	
80BA51960188 - 0..5/6A	
A1U2.2 / IMU02-62F1150	current transducer
IMU02-A1U2.2 62F2351	AC current transducer
IMU02-62F1150 A1U2.2	Current transducer
644.1241 / PIR 24-1	
644.1245 / PIR 24-5	
644.1255 / PIR 25-5	
652.03.121500	LED switch position indicator
80BA54190419 / EQ72K; MB + Sk: 0..500V	
VUW4.0	